

S/N 10/791,305

Page 3

ESKO-038US

AMENDMENT(S) TO THE CLAIMS:

The following listing of claims will replace all prior versions, and listings, of claims on the application. All claims are set forth below with one of the following annotations.

- (Original): Claim filed with the application.
- (Currently amended): Claim being amended in the current amendment paper.
- (Canceled): Claim cancelled or deleted from the application. No claim text is shown.
- (Withdrawn): Claim still in the application, but in a non-elected status.
- (New): Claim being added in the current amendment paper.
- (Previously presented): Claim added or amended in an earlier amendment paper.
- (Not entered): Claim presented in a previous amendment, but not entered or whose entry status unknown. No claim text is shown.

1. (Cancelled).
2. (Currently amended) An apparatus as recited in ~~claim 1~~ claim 7, wherein each compartment, when at its loading vertical position, is movable horizontally from and to the rest horizontal position to and from a loading horizontal position suitable for loading and unloading the plate on the compartment onto and from the imager.
3. (Currently amended) An apparatus as recited in ~~claim 1~~ claim 7, wherein the lifting mechanism is operative to lift and lower the magazine of compartments, and wherein the control system controls the lifting and lowering of the magazine until a selected one of the compartments is at its loading vertical position.
4. (Currently amended) An apparatus as recited in ~~claim 1~~ claim 7, wherein the lifting mechanism is operative to lift and lower the compartments of the magazine one compartment at a time.
5. (Currently amended) ~~An apparatus as recited in claim 4,~~ An apparatus to aid loading and unloading of flexographic plates to and from an imager, comprising:

S/N 10/791,305

Page 4

ESKO-038US

a magazine containing a plurality of compartments each for holding a single flexographic plate, the compartments arranged vertically, and movable in a vertical direction, each respective compartment having a respective rest vertical position at a rest horizontal position, each respective compartment further having a loading vertical position at which the respective compartment is at a height for loading onto the imager;

a lifting mechanism to lift and lower the compartments; and

a control system to control the lifting and lowering by the lifting mechanism,

such that a particular compartment is moved from its rest vertical position at the rest horizontal position to the loading vertical position at which the particular compartment is at the height for loading onto the imager or unloading from the imager,

wherein each compartment, when at its loading vertical position, is movable horizontally from and to the rest horizontal position to and from a loading horizontal position configured for loading and unloading the plate on the compartment onto and from the imager, respectively,

wherein the lifting mechanism is operative to lift and lower the compartments of the magazine one compartment at a time, and

wherein the respective rest vertical positions of each of the compartments are lower than the loading vertical position such that a particular compartment pre-loaded with a plate is lifted from its rest vertical position to the loading vertical position, then moved while at the loading vertical position to the loading horizontal position for loading onto the imager.

6. (Currently amended) An apparatus as recited in claim 1, An apparatus to aid loading and unloading of flexographic plates to and from an imager, comprising:

S/N 10/791,305

Page 5

ESKO-038US

a magazine containing a plurality of compartments each for holding a single flexographic plate, the compartments arranged vertically, and movable in a vertical direction, each respective compartment having a respective rest vertical position at a rest horizontal position, each respective compartment further having a loading vertical position at which the respective compartment is at a height for loading onto the imager;

a lifting mechanism to lift and lower the compartments; and

a control system to control the lifting and lowering by the lifting mechanism.

such that a particular compartment is moved from its rest vertical position at the rest horizontal position to the loading vertical position at which the particular compartment is at the height for loading onto the imager or unloading from the imager,

wherein each compartment has an imaged vertical position, and wherein the lifting mechanism is further operative to lift or lower the particular compartments each from the respective loading vertical position after the plate is imaged and unloaded from the imager to the respective imaged vertical position of the particular compartment.
~~compartment's respective imaged vertical position.~~

7. (Currently amended) An apparatus as recited in claim 1, An apparatus to aid loading and unloading of flexographic plates to and from an imager, comprising:

a magazine containing a plurality of compartments each for holding a single flexographic plate, the compartments arranged vertically, and movable in a vertical direction, each respective compartment having a respective rest vertical position at a rest horizontal position, each respective compartment further having a loading vertical position at which the respective compartment is at a height for loading onto the imager;

a lifting mechanism to lift and lower the compartments; and

S/N 10/791,305

Page 6

ESKO-038US

a control system to control the lifting and lowering by the lifting mechanism,

such that a particular compartment is moved from its rest vertical position at the rest horizontal position to the loading vertical position at which the particular compartment is at the height for loading onto the imager or unloading from the imager,

wherein the compartments are ~~pre-loaded~~ loaded, each with one pre-sensitized CTP flexographic plates, ~~plate~~ such that as a result of the pre-loading, the particular plate is in the compartment without a cover sheet.

8. (Currently amended) An apparatus as recited in ~~claim 1~~ claim 7, wherein the magazine is transportable from a storage location to an imaging location adjacent to the imager.
9. (Currently amended) An apparatus as recited in ~~claim 1~~ claim 7, wherein the magazine comprises at least 10 compartments.
10. (Cancelled).
11. (Currently amended) A method as recited in ~~claim 10~~ claim 15, further comprising:
 - (c) moving the particular compartment when at its loading vertical position from and to its rest horizontal position to and from a loading horizontal position suitable for loading and unloading the plate on the compartment onto and from the imager.
12. (Currently amended) A method as recited in ~~claim 10~~ claim 15, wherein step (b) includes lifting or lowering the magazine of compartments until the particular compartment of the particular flexographic plate is at its loading vertical position.
13. (Currently amended) A method as recited in ~~claim 10~~ claim 15, wherein step (b) includes lifting or lowering only the particular compartment of the magazine on the basis of one compartment being lifted or lowered at a time.

S/N 10/791,305

Page 7

ESKO-038US

14. (Currently amended) ~~A method as recited in claim 13;~~ A method of loading a flexographic plate to an imager, the method comprising:

(a) pre-loading a particular flexographic plate into a particular compartment of a magazine containing a plurality of compartments each for holding a single flexographic plate, the compartments arranged vertically, and movable in a vertical direction, each respective compartment having a respective rest vertical position at a rest horizontal position, each respective compartment further having a loading vertical position at which the respective compartment is at a height for loading onto the imager or unloading from the imager; and

(b) lifting or lowering the particular compartment from its rest vertical position at its rest horizontal position to its loading vertical position,

such that the particular flexographic plate can be loaded onto the imager,

wherein each compartment, when at its loading vertical position, is movable horizontally from and to the rest horizontal position to and from a loading horizontal position suitable for loading and unloading the plate on the compartment onto and from the imager,

wherein step (b) includes lifting or lowering only the particular compartment of the magazine on the basis of one compartment being lifted or lowered at a time, and

wherein the respective rest vertical positions of each of the compartments are lower than the loading vertical position such that step (b) includes lifting the pre-loaded particular compartment from its rest vertical position to the loading vertical position, then moving the particular compartment while at the loading vertical position to the loading horizontal position for loading the plate onto the imager.

15. (Currently amended) ~~A method as recited in claim 10;~~ A method of loading a flexographic plate to an imager, the method comprising:

S/N 10/791,305

Page 8

ESKO-038US

(a) pre-loading a particular flexographic plate into a particular compartment of a magazine containing a plurality of compartments each for holding a single flexographic plate, the compartments arranged vertically, and movable in a vertical direction, each respective compartment having a respective rest vertical position at a rest horizontal position, each respective compartment further having a loading vertical position at which the respective compartment is at a height for loading onto the imager or unloading from the imager; and

(b) lifting or lowering the particular compartment from its rest vertical position at its rest horizontal position to its loading vertical position,

such that the particular flexographic plate can be loaded onto the imager, the method further comprising:

lifting or lowering the particular compartment from the loading vertical position after the plate is imaged and unloaded from the imager to an imaged vertical position for the particular compartment.

16. (Currently amended) A method as recited in claim 10; A method of loading a flexographic plate to an imager, the method comprising:

(a) pre-loading a particular flexographic plate into a particular compartment of a magazine containing a plurality of compartments each for holding a single flexographic plate, the compartments arranged vertically, and movable in a vertical direction, each respective compartment having a respective rest vertical position at a rest horizontal position, each respective compartment further having a loading vertical position at which the respective compartment is at a height for loading onto the imager or unloading from the imager; and

(b) lifting or lowering the particular compartment from its rest vertical position at its rest horizontal position to its loading vertical position,

S/N 10/791,305

Page 9

ESKO-038US

such that the particular flexographic plate can be loaded onto the imager, wherein step (a) includes pre-loading the particular compartment with a pre-sensitized CTP flexographic plate such that as a result of the pre-loading, the particular plate is in the compartment without a cover sheet.

17. (Currently amended) A method as recited in ~~claim 10~~ claim 15, further comprising transporting the magazine from a storage location to an imaging location adjacent to the imager.
18. (Currently amended) A method as recited in ~~claim 10~~ claim 15, wherein the magazine comprises at least 10 compartments.
19. (Currently amended) A method as recited in ~~claim 10~~ claim 15, wherein step (b) is carried out under a computerized control system.